

Nanjing Goolinked Metal Technology

Accessories 配件 Product Catalog

Accessories 配件

Product Overview

We supply a complete range of wire rope accessories and fittings for termination, connection, tensioning, and protection. All products are manufactured to international standards with material certifications available.

Product Categories

1. Wire Rope Clips (钢丝绳夹)

Type	Description	Rope Diameter	Standard
Malleable Iron Clip (马钢夹)	Economy type, light duty	3–60 mm	GB/T 5976
Forged Clip (锻造夹)	Heavy duty, forged steel	3–60 mm	US Federal Spec FF-C-450
Heavy Duty Clip (重型夹)	Precision cast, highest strength	3–60 mm	EN 13411-5
Stainless Steel Clip (不锈钢夹)	304/316 SS, corrosion resistant	3–32 mm	DIN 1142

[Wire-Rope-Clips](#)

2. Thimbles (套环/鸡心环)

Type	Description	Rope Diameter	Standard
Standard Thimble (普通套环)	Light duty, general purpose	3–60 mm	GB/T 5974
Heavy Duty Thimble (重型套环)	Forged or cast, high load	6–80 mm	DIN 6811
Stainless Steel Thimble (不锈钢套环)	304/316 SS, marine grade	3–32 mm	EN 13411-1

[Thimbles](#)

3. Shackles (卸扣)

Type	Description	WLL Range	Standard
Bow Shackle / Anchor Shackle (弓型卸扣)	Wide opening, multi-leg sling use	0.33–55 t	GB/T 25854 / ISO 2415
Dee Shackle / Chain Shackle (D型卸扣)	Narrow opening, inline loading	0.33–55 t	GB/T 25854 / ISO 2415
Screw Pin Shackle (螺栓型卸扣)	Hand-tightened pin	0.33–55 t	ISO 2415
Bolt-Nut-Cotter Shackle (螺母销型卸扣)	Bolt with nut and cotter pin, permanent	0.33–55 t	ISO 2415
Stainless Steel Shackle (不锈钢卸扣)	304/316 SS	0.15–12 t	ISO 2415

[Shackles](#)

4. Turnbuckles (花篮螺丝/螺旋扣)

Type	Description	Size Range	Standard
Eye & Eye Turnbuckle (OO型)	Two eye ends	M6–M80	DIN 1480
Hook & Hook Turnbuckle (CC型)	Two hook ends	M6–M48	DIN 1480
Eye & Hook Turnbuckle (OC型)	One eye, one hook	M6–M48	DIN 1480

Jaw & Jaw Turnbuckle (JJ型)	Two jaw ends with pins	M6–M80	DIN 1480
Stainless Steel Turnbuckle (不锈钢)	304/316 SS	M3–M24	DIN 1480

[Turnbuckles](#)

5. Wedge Sockets (楔形接头)

Type	Description	Rope Diameter	Standard
Standard Wedge Socket (普通楔形接头)	Cast steel body with wedge	6–64 mm	GB/T 5973
Safety Wedge Socket (安全楔形接头)	With safety latch/bolt	10–48 mm	EN 13411-6

[Wedge-Sockets](#)

6. Swage Sleeves / Ferrules (铝套/压制套管)

Type	Description	Rope Diameter	Material
Oval / Figure-8 Sleeve (8字型铝套)	Single hole, standard loop	1–40 mm	Aluminum / Copper
Double Hole Sleeve (双孔铝套)	Two holes for turn-back eye	1–40 mm	Aluminum / Copper
Stop Sleeve / Button Stop (定位铝套)	Single hole, stops rope end	1–20 mm	Aluminum / Steel
Stainless Steel Sleeve (不锈钢套管)	304/316 SS	1–16 mm	Stainless Steel

[Swage-Sleeves](#)

7. Hooks (吊钩)

Type	Description	WLL Range	Standard
Eye Hook (环眼吊钩)	With safety latch	0.5–50 t	EN 1677
Clevis Hook (销轴吊钩)	With pin connection	0.5–30 t	EN 1677
Swivel Hook (旋转吊钩)	With bearing swivel	1–30 t	EN 1677
S-Hook (S型钩)	Light duty, no latch	0.1–5 t	—
Grab Hook (抓钩)	For chain, no latch	1–15 t	EN 1677

[Hooks](#)

8. Sockets / Spelter Sockets (浇注索节)

Type	Description	Rope Diameter	Standard
Open Socket (开式索节)	Open body with pin	10–120 mm	EN 13411-4
Closed Socket (闭式索节)	Closed eye, permanent	10–120 mm	EN 13411-4
Fork Socket (叉型索节)	Fork end with pin	10–80 mm	EN 13411-4

[Spelter-Sockets](#)

Surface Finishes

- Hot-dip galvanized (热镀锌)
- Electro-galvanized (电镀锌)
- Self-color / Black (光面/发黑)
- Stainless steel 304 / 316 (不锈钢)
- Painted (喷漆)
- Powder coated (喷塑)

Certificates & Compliance

- Material test certificates (MTC) EN 10204 3.1
 - Proof load test certificates
 - ISO 9001, CE, BV, DNV, ABS, LR certifications available
 - Third-party inspection accepted
-

File Structure

Each product category has its own folder containing: - images/ — 4 product images (structure diagram, product photo, application photo, detail photo), 1000×1000px with goolinked watermark - *-Specification.docx — Detailed product specification document with embedded images

```
配件/  
├─ catalog.md  
├─ Wire-Rope-Clips/  
│   ├─ images/ {cross-section, product, application, detail}.jpg  
│   └─ Wire-Rope-Clips-Specification.docx  
├─ Thimbles/  
├─ Shackles/  
├─ Turnbuckles/  
├─ Wedge-Sockets/  
├─ Swage-Sleeves/  
├─ Hooks/  
└─ Spelter-Sockets/
```
